

task_kyt15w11e3sempb2_with_calculation

Student Group

First Name	Surname	Matrikel Nr.

Table of Contents

Exercise E1 Resistivity and temperature dependent Resistance (written test, approx. 7 % of a 60-minute written test, SS2023) 2

resistivity, power, exam ee1 SS2023

Exercise E1 Resistivity and temperature dependent Resistance (written test, approx. 7 % of a 60-minute written test, SS2023)

[illegible]

Solution
The resistivity of the dielectric material is $\rho_{\text{PP}}(20 \sim \text{°C}) = 10^{17} \sim \Omega \cdot \text{m}$.

For the given material the temperature coefficients in the range of $0 \sim 20^\circ\text{C}$ and $55 \sim 100^\circ\text{C}$ are given as $\alpha = -0.048 \sim 1/\text{K}$ and $\beta = +0.00057 \sim 1/\text{K}^2$.

$$\begin{aligned} R(55 \sim \text{K}) &= R(20 \sim \text{K}) \cdot (1 + \alpha \cdot \Delta T + \beta \cdot T^2 + \dots) \\ &= 80 \sim \text{G}\Omega \cdot (1 - 0.048 \sim \text{K} + 0.00057 \sim \text{K}^2 \cdot \Delta T) \end{aligned}$$

Calculate the resistance for the dielectric material for $20 \text{ }^\circ\text{C}$.

Solution

$$\begin{aligned} R(20 \text{ }^\circ\text{C}) &= \rho \cdot \frac{d}{A} \\ &= 10^{17} \text{ }^\circ\text{C} \cdot \frac{0.8 \cdot 10^{-6} \text{ m}}{1 \text{ m}^2} \end{aligned}$$

From:

<https://first.mexle.te.hs-heilbronn.de/> - **MEXLE Wiki**

Permanent link:

https://first.mexle.te.hs-heilbronn.de/ee1/task_kyt15w11e3sempb2_with_calculation

Last update: **2023/11/08 11:26**

